

Waterproof No Touch Button

No Touch

Round

No Touch

Ellipse

User Manual

Main Features

> IP66 waterproof

> Zinc-alloy housing

> Output contact: NO/NC/COM

> Sensor distance: 3~10cm (Adjustable)

> Red LED indicator: standby

> Green LED indicator: active

> 5s, 10s or Toggle Mode Timer Delay (Optional)

Specifications

Operating Voltage	10~24V DC
Idle Current	≤15mA
Working Current	≤25mA
Sensor Distance	3~10cm (Adjustable)
Output	NC or NO
Infrared Wavelength	940 nm
Timer Delay (Optional)	5s / 10s / Toggle Mode
Environment	IP66 Waterproof
Operating Temperature	-20℃~+60℃
Operating Humidity	0%~86%
Physical	Zinc-alloy
Dimension	Diameter: 73mm, Thickness: 20mm (Round) L105 x W69 x H20 mm(Ellipse)
Unit Weight	150g(Round) 200g(Ellipse)
Shipping Weight	210g(Round) 260g(Ellipse)

- 01 -

Wiring

Wire Color	Function	Notes
Red	Power +	10~24 Volts DC
Black	GND	Ground
Green	NC	Normally Closed
Brown	COM	Common
White	NO	Normally Open

Sensor Distance and Timer Delay (Optional) Adjustment

ON

1 2

1→ON = 5s

2→ON = 10s

1→ON + 2→ON = Toggle Mode

Sensor Distance 3~10 cm

Timer Delay (Optional Function)

- 02 -

Packing List

Item	Quantity
Gift Box	1
No Touch Button	1
Manual	1
Self Tapping Screw	2
Wall Fixing Plug	2